

**NEW!**

# LW SC-400 ES



Compressors

**NEW!**

# LW SC-400 ES

**Compressors**

## Specifications

- » Electro motor
- » Powder coated steel housing (RAL 7016)
- » Sound insulated housing
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Hour counter
- » Operating panel with start/stop and condensate test button, as well emergency stop switch
- » Motor protection switch
- » Safety switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » 3 x concentric suction/pressure valves
- » Low pressure oil pump and filter
- » Oil- / Water separators after each stage
- » Safety valves after each stage
- » Maintenance door on both sides
- » High pressure outlet with 3000 mm hose
- » Filling pressure of your choice (200 or 300 bar)
- » Breathing air purification an accordance to EN 12021

## Options

- » Auto start system
- » Up to 6 additional hoses available
- » 4- fold filling panel installed at front door
- » 200 and 300 bar parallel filling pressures
- » Phase monitoring c/w shut down at wrong direction of rotation
- » Ambient temperature monitoring
- » Oil pressure gauge
- » Intermediate pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » Indicator light - service interval
- » Cylinder head temperature monitoring with auto shut down
- » Oil temperature display with auto shut down
- » 2.3 ltr. Filter housing (Filter capacity: 1200 m<sup>3</sup> at +20°C)
- » Puracon filter monitoring
- » Remote Tab Control - RTC
- » Power cable and plug
- » Special voltages / frequencies on request

## Technical Data

LW SC-400 ES	
Type:	Air cooled piston compressor
Charging rate * [litre/min] / [Nm <sup>3</sup> /h] / [cfm]:	400 / 24 / 14.1
Max. Pressure [bar]:	350
RPM [1/min]:	800
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor
Drive power [kW] with 50 Hz / 60 Hz:	11.0 / 13.2
Cooling air req. [m <sup>3</sup> /h] with 50 Hz / 60 Hz:	3300 / 3960
Lubrication type:	Oil pump
Oil capacity [litre]:	2.7
Oil pressure [bar]:	1.5 (+/- 0.2)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m <sup>3</sup> at +20°C] <sup>1)</sup> :	900 (at +20°C / approx. 37.5 h)
Dimensions W x D x H [mm]:	860 x 1600 x 2000
Weight [kg]:	447
Noise level (measured at 1 m) [dB(A)]:	70

\* Measured by tank filling (10 l) from 0 - 200 bar, ± 5%.

<sup>1)</sup> In accordance with EN 12021



**เครื่องอัดอากาศ LW**  
by JST Engineering  
LW compressors  
Authorized agent  
in Thailand

\* เครื่องอัดอากาศ LW  
ในประเทศไทยมีอยู่ 2 รุ่น

**JST ENGINEERING CO.,LTD.** 

78/6 MOO 7 KINGKAEW RD., RACHATEWA,  
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.

คุณวิโรจน์ 081-684-0565  
คุณฉัตรเทพ 098-825-8600  
คุณฉัตรภรณ์ 092-247-6565

  
Facebook Page

+66 (0) 2738 5050-4    URL: www.jst.co.th  
+66 (0) 2738 5055    LINE ID: alithep.jst  
Info@jst.co.th    www.facebook.com/LWCompressor