

**NEW!**

# LW SC-900 E



Compressors



**NEW!**

# LW SC-900 E



## Specifications

- » Electro motor
- » Powder coated steel frame (RAL 7016)
- » Powder coated steel fan guard (RAL 7016)
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Inclusive a remote control box for wall mounting
- » Main-, Start/Stop- and condensate test buttons, as well as emergency stop switch
- » Hour counter
- » Oil pressure gauge
- » Oil pressure monitoring c/w auto shut down
- » High pressure outlet with 1500 mm hose
- » Motor protection switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 4 x concentric suction/pressure valves
- » Filling pressure of your choice (200 or 300 bar)
- » Breathing air purification in accordance to EN 12021

## Options

- |   |   |
|---|---|
| » Auto start system   | » Ambient temperature monitoring            |
| » Oil temperature display with auto shut down                   | » Puracon filter monitoring                 |
| » Cylinder head temperature monitoring with auto shut down      | » Remote Tab Control - RTC                  |
| » Intermediate pressure gauges                                  | » Power cable and plug                      |
| » Phase monitoring c/w shut down at wrong direction of rotation | » Special voltages / frequencies on request |
| » Indicator light - service interval                            |   |

## Technical Data

LW SC-900 E	
Type:	Air cooled piston compressor
Charging rate * [litre/min] / [Nm³/h] / [cfm]:	900 / 54 / 31.8
Max. Pressure [bar]:	350
RPM [1/min]:	1260
No of cylinders / No of stages:	4 / 4
Prime mover type:	E-Motor
Drive power [kW] with 50 Hz / 60 Hz:	18.5 / 22.2
Cooling air req. [m³/h] with 50 Hz / 60 Hz:	5550 / 6660
Lubrication type:	Oil pump + Splash oil
Oil capacity [litre]:	5
Oil pressure [bar]:	4.0 (+/- 0.5)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m³ at +20°C] <sup>1)</sup> :	2400 (at +20°C / approx. 44.4 h)
Dimensions W x D x H [mm]:	1670 x 770 x 1170
Weight [kg]:	625
Noise level (measured at 1 m) [dB(A)]:	88

\* Measured by tank filling (10 l) from 0 - 200 bar, ± 5%.

<sup>1)</sup> In accordance with EN 12021



JST ENGINEERING CO., LTD.

7/6 MOO 7 KINGKAEW RD, RACHATEWA,  
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.



คุณวิรบุนน์ 081-684-0565

คุณอุดมเรว 098-825-8600

คุณจักรกิตติ์ 092-247-6565

Facebook Page

	+66 (0) 2738 5050-4		URL: www.jst.co.th
	+66 (0) 2738 5055		LINE ID: attthep.jst
	info@jst.co.th		www.facebook.com/LWCompressor

#เรื่องของคุณเราคุ้นเคย  
ในชีวิตประจำวัน