

NEW!

LW SC-400 E



Compressors

NEW!

LW SC-400 E



Specifications

- » Electro motor
- » Powder coated steel housing (RAL 7016)
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Hour counter
- » Operating panel c/w start/stop and condensate test buttons, as well as emergency stop switch
- » 4x Filling hose c/w filling valve
- » Motor protection switch
- » Safety switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 3 concentric suction/pressure valves
- » Filling pressure of your choice (200 or 300 bar)
- » Connections to your choice (DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- | | |
|---|--|
| » Auto start system | » Cylinder head temperature monitoring with auto shut down |
| » 200 and 300 bar parallel filling pressures | » Oil temperature display with auto shut down |
| » Phase monitoring c/w shut down at wrong direction of rotation | » Puracon filter monitoring |
| » Ambient temperature monitoring | » Remote Tab Control - RTC |
| » Oil pressure gauge | » Additional high pressure outlet |
| » Intermediate pressure gauges | » Power cable and plug |
| » Oil pressure monitoring c/w auto shut down | » Special voltages / frequencies on request |
| » Indicator light - service interval | |

Technical Data

LW SC-400 E	
Type:	Air cooled piston compressor
Charging rate * [litre/min] / [Nm³/h] / [cfm]:	400 / 24 / 14.1
Max. Pressure [bar]:	350
RPM [1/min]:	900
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor
Drive power [kW] with 50 Hz / 60 Hz:	11.0 / 13.2
Cooling air req. [m³/h] with 50 Hz / 60 Hz:	3300 / 3960
Lubrication type:	Oil pump
Oil capacity [litre]:	2.7
Oil pressure [bar]:	1.5 (+/- 0.2)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m³ at +20°C] ¹⁾ :	900 (at +20°C / approx. 37.5 h)
Dimensions W x D x H [mm]:	1540 x 730 x 1020
Weight [kg]:	350
Noise level (measured at 1 m) [dB(A)]:	82

* Measured by tank filling (10 l) from 0 - 200 bar, ± 5%.

¹⁾ In accordance with EN 12021



JST ENGINEERING CO., LTD.

78/6 MOO 7 KINGKAEW RD. RACHATEWA,
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.



ศูนย์บริการ JST
ประเทศไทย

081-684-0565

ศูนย์บริการ JST
ประเทศไทย

098-825-8600

ศูนย์บริการ JST
ประเทศไทย

092-247-6565



Facebook Page

โทรศัพท์: +66 (0) 2738 5050-4 | URL: www.jst.co.th

โทรศัพท์: +66 (0) 2738 5055 | LINE ID: atthep.jst

อีเมล: info@jst.co.th | Facebook Page