

# Puracon Stationary PRO



## Puracon Stationary PRO

Puracon Stationary PRO is the professional solution for humidity monitoring during the filling procedure. The PRO version provides separated sensor and display unit. The sensor is connected directly to the high-pressure line after the humidity filter and is linked to the display unit via a data cable.

### Specifications

- » Aluminum sensor housing with G $\frac{1}{4}$ " inlet and outlet
- » Display unit ( $\varnothing$  96 x 37 mm) for wall mounting with sensor cable (length: 2 m)
- » Power supply cable (length: 1.7 m) with CE plug 100 - 230 V ~ 50/60Hz
- » Digital LCD display with humidity display in mg/m $^3$  and error warnings
- » Higher accuracy by new temperature and pressure compensation
- » 2 monitoring LEDs, adjustable limits
- » 2 output signals (24V)
- » Sensor cables with 5, 10, 15 or 30 m available for surcharge
- » Approved up to 350 bar

### Available versions

- » 420 bar sensor (stainless steel)
- » 12 V DC
- » 24 V DC
- » Ex with ATEX certification



## Technical Data

Technical Data	Puracon Stationary PRO
Operating pressure	150 - 350 bar / optional 420 bar
Power supply	100 - 240 V / optional 12V or 24VDC
Connector	Sensor: G1/4 thread
Protection rating	IP64
Operating temperature	+5°C to +45°C



เครื่องอัดอากาศ LW  
by JST Engineering  
LW compressors  
Authorized agent  
in Thailand

บริษัท อีเอสที เอ็นจิเนียริ่ง จำกัด  
10540 THAILAND

**JST ENGINEERING CO.,LTD.**

78/6 MOO 7 KINGKAEW RD., RACHATEWA,  
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.

คุณวิโรจน์ 081-684-0565  
คุณอดิเทพ 098-825-8600  
คุณฉัตรกัม 092-247-6565

Facebook Page



☎ +66 (0) 2738 5050-4    🌐 URL: www.jst.co.th  
☎ +66 (0) 2738 5055    📧 LINE ID: atthepjst  
✉ info@jst.co.th    🌐 www.facebook.com/LWCompressor